

2


1

SINGLE POST


SINGLE POST

DOUBLE POST


DOUBLE POST




BOTH FITTING ATTACHED TO FACE



ONE FITTING ATTACHES THROUGH POST AND OTHER ATTACHES TO FACE




BOTH FITTINGS ATTACH TO FACE




CABLE RUNS CONTINUOUSLY THROUGH THE CORNER

SINGLE POST




BOTH FITTINGS ATTACHED THROUGH POST. MUST OFFSET DRILL HOLES BY AT LEAST 1/2"

SINGLE POST



BOTH FITTINGS ATTACHED THROUGH POST



MAINTAIN 5'-0" MAX. SPACING BETWEEN POSTS TO MINIMIZE CABLE DEFLECTION

NOTE. SPACING BETWEEN FACIA MOUNT HOLES MUST EXCEED 7 INCHES

NOTE. SPACING BETWEEN CENTER OF BOTTOM HOLE AND BOTTOM OF POST MUST BE AT LEAST 2.5"



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAINLESS CABLE AND RAILING®. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAINLESS CABLE AND RAILING® IS PROHIBITED.

NOTES: UNLESS OTHERWISE SPECIFIED

1. DIMENSIONS SHOWN - INCHES [MM].
2. MACHINED SURFACES TO BE 63μIN MAX.
4. PART TO BE FREE OF BURRS AND SHARP EDGES.
5. ALL MATERIAL TO BE CLEAN, DEGREASED AND FREE OF ALL IMPURITIES.
6. ANY CHANGE MUST BE AUTHORIZED BY AN SC&R ENGINEER.

DIMENSIONS ARE IN INCHES
FRACTIONAL ±
ANGULAR: MACH ±
TWO PLACE DECIMAL ±
THREE PLACE DECIMAL ±

MATERIAL

FINISH

DO NOT SCALE DRAWING

DRAWN

NAME

JC

DATE

01/31/2017

ENG APPR.

MFG APPR.

COMMENTS:

BUILDING CODES VARY BY CITY & COUNTRY. FOLLOW THE INSTALLATION AND RAILING DESIGN INSTRUCTIONS AS DETAILED IN THIS DRAWING. DOES NOT GUARANTEE CODE COMPLIANCE IN ALL AREAS. BEFORE STARTING THE PROJECT, CHECK LOCAL REQUIREMENTS FOR USING AND INSTALLING CABLE RAILINGS.

TITLE:

DESIGN RECOMMENDATION: STAINLESS STEEL SQUARE TUBE WITH CABLE INFILL FASCIA MOUNTED.

SIZE

A

DWG. NO.

REV

SCALE: 1:20

WEIGHT:

SHEET 1 OF 1

2

1